



BACK-UP ALARMS



FEP

252
254
256258
260

> Features

- Sealed, solid-state electronics.
- Universal mounting capability.
- Polarity and voltage spike protection.
- 60 pulse/minute sound cycle.

> Approvals

- Some models meet SAE Class B and Class C

Federal Signal back-up alarms are dependable, affordable alarms ideal for use on ambulances, fire apparatus, or utility/construction vehicles. Each of the models features a glass reinforced nylon housing for long-lasting durability that can be steam cleaned. The alarms have an operating temperature range of -40°F to +170°F.

Model FEP – 97 decibels

Sealed against the elements, the FEP Evacuator® Plus back-up alarm comes with a dual-function feature allowing users to choose from a “pulse” tone, which is an intermittent signal primarily used for back-up warning, or a “constant-on” tone, which is a solid signal that can be used to signal motion such as a truck platform lifting or moving outriggers.

Model 252 – 97 decibels

The model 252 is a multiple voltage alarm specifically designed for electric powered vehicles. Meets SAE J994, Class C specification.

Model 254 – 87 decibels

The model 254 is a dependable, affordable alarm that operates at 12 volts.

Model 256 – 97 decibels

The model 256 multiple voltage alarm is dependable and compact. Meets SAE Class C.

Model 258 – 107 decibels

The model 258 is a versatile alarm that mounts vertically or horizontally. Meets SAE Class B.

Model 260 – 87-112 decibels

The model 260 alarm features solid-state electronics that automatically adjust to changing noise environments. The alarm self-adjusts to a minimum of 5dB above surrounding noise levels.

> How to Order

Specify Model

- FEP** Evacuator Plus, 97dB, dual function, 12-48 VDC
- 252** 97dB, 12-48 VDC
- 254** 87dB, 12 VDC
- 256** 97dB, 6-36 VDC
- 258** 107dB, 6-36 VDC
- 260** 87-112dB, 12-24 VDC

	FEP	252	254	256	258	260
Specifications						
Volts	12-48	12-48	12	6-36	6-36	6-36
Sound Output	97dB	97dB	87dB	97dB	107dB	87-112dB
Amp Draw	0.09A	0.2A	0.3A	0.3A	0.5A	1.0A
Ship Weight						
	0.6 lbs (0.3 kg)	1.0 lbs (0.5 kg)	1.0 lbs (0.5 kg)	1.0 lbs (0.5 kg)	2.0 lbs (0.9 kg)	2.0 lbs (0.9 kg)
Physical Specifications						
Width	2.9 in (7.3 cm)	4.0 in (10.2 cm)	4.0 in (10.2 cm)	4.0 in (10.2 cm)	5.0 in (12.7 cm)	5.0 in (12.7 cm)
Height	2.9 in (7.3 cm)	3.0 in (7.6 cm)	3.0 in (7.6 cm)	3.0 in (7.6 cm)	4.0 in (10.2 cm)	4.0 in (10.2 cm)
Depth	2.4 in (6.0 cm)	1.5 in (3.8 cm)	1.5 in (3.8 cm)	1.5 in (3.8 cm)	3.0 in (7.6 cm)	3.0 in (7.6 cm)

